


REV	DATE	DESCRIPTION	INIT
1	10.11.2019	created drawing	DM

Electrical Properties:
 1. It should have no any open or short, Miswiring, or intermittent failures.
 2. The cable shall be 100% electrically tested.

RoHS

From	Pin#	To	Pin#
T1	Red	J1	1
T2	Gray	J1	2



Terminal Type	Crimping Specification	Wire Type	Crimp Height	Crimp Width	Pull Force
39-00-0040	18-24#	20#	1.05±0.10	1.55±0.20	≥6.5Kfg

No	Material	Description	Qty	MNF.Name
1	Wire	UL1007 20AWG, 80°C 300V	2Pcs	YD
2	Terminal	39-00-0040	2Pcs	Molex
3	Housing	39-01-2021	1Pc	Molex
4	Terminal	ST1100502-25C, 2.8*0.5mm, Tin plated, Non-insulated	2Pcs	QW
5	H/S/T	UL black heat shrink tubing	2Pcs	Woer

		Elektrosil GmbH	
		Ruhstraße 53 22761 Hamburg	
DRAWN BY DM	DATE 10.11.2019	MATERIAL xxx	DRAWING TITLE EM-50.0582
CHECKED BY JK	DATE 11.11.2019	SIZE A2	DRAWING NUMBER EM50.0582.001.A
DESIGNED BY ET	DATE 07.11.20109	SCALE 1:2	WEIGHT(kg) XXX
		SHEET 1/1	